



CLASSIC-V VS. SUPER-V:
What's the difference? We've drawn on decades of rack mount case experience to produce two tiers of performance.

The Pelican-Hardigg™ Classic-V Series has a 33" (838 mm) depth frame

and has longer shock mounts and a larger sway space between the rack and shell. This case also has 4 removable heavy-duty casters and stainless steel handles. Extra insurance if your equipment frequently ships via freight services.

The Pelican-Hardigg™ Super-V Series has a 24" (610 mm) deep frame and uses shorter shock mounts for compact case dimensions. This case uses edge casters - just grab the Comfort-Grip Handles and you're ready to roll.

SHARED FEATURES
All Pelican-Hardigg™ Classic-V and Super-V Series are rated for equipment loads up to 77 kg. Mating columnar ribs create a rigid shell and also provide secure stacking of same-size cases.



You'll also find a manual purge valve, so air pressure in the case can be equalised to the atmosphere. This prevents vacuum-lock that can make opening the case difficult. Lids include a fully sealed

O-ring gasket that works with the purge valve to make the case fully watertight.

These features may seem extraordinary, but we've learned that water and electronics don't mix.

Look for detailed dimensions and features on the following pages and on Peli.com/racks



TO SEE THE FULL LINE OF RACK MOUNT CASES GO TO: PELI.COM/RACKS



Classic Rack



SuperMac™



Mac Rack™



Black Box



ProRack™

NEW PELI-HARDIGG™ V-SERIES RACK MOUNT CASES



IN STOCK AND READY TO ROCK



INTRODUCING PELI-HARDIGG™ V-SERIES

Fabrieksdistributeur sinds 1989:
Vonk B.V
Voorstraat 41, 3265 BT PIERSHIL
www.vonkbv.com
info@vonkbv.com
Tel. +31-(0)88-0330300
Kom eens langs. Ruime Voorraad aanwezig.

THE OFF-THE-SHELF RACK MOUNT CASE WITH PRO-GRADE FEATURES. Gearing up for an event? Now you can get pro-grade rack mount cases straight away. The Pelican-Hardigg V-Series Cases are the perfect companion for the music, AV, entertainment, news and drones industry.



the clip nut onto a square hole and you've got a secure, threaded mount. We even ship the case with your choice of 10-32 Imperial or M6 Metric clip-nuts.



Pelican-Hardigg™ V-Series Cases are built utilizing a full-boxed 19" (482 mm) steel rack with a industry-standard square hole pattern, so hanging electronics with tab mounts is a snap. These cases also include clip nuts- just attach

VIBRATION IS YOUR ENEMY. Drops and impact are an obvious no-no with electronics, but vibration puts damaging repetitive stress on delicate parts and soldered joints. That's why you'll find 8 heavy duty rubber shock mounts to isolate the frame inside the shell. The polymer outer shell absorbs impacts, and the shock mount inside dissipates residual movement. Rack mount cases without shock mounts transfer impact forces directly to the electronics inside.



PELI-HARDIGG™ 24" SUPER-V RACK MOUNT CASE

PELI-HARDIGG™ 33" CLASSIC-V RACK MOUNT CASE



Stainless steel retractable handles



4 Removable heavy duty bottom casters



Moulded Comfort Grip Handles are easy to use with gloves



Moulded in edge casters are always r allow case sta without r casters

ROTO MOULDED CASES

PELI 1 YEAR LIMITED GUARANTEE

Pelican Products, S.L.U. ("Peli") guarantees its rotationally moulded containers will be free of defects in materials and workmanship for a period of one year from the date of purchase. This warranty does not cover any associated hardware including closure hardware, retractable handles, wheels, and fasteners, which Pelican warrants against defects in materials and workmanship for a period of 90 days from the date of purchase. This warranty applies only to the original purchaser and is not transferable. To the extent permitted by law: Pelican's liability is limited to the case and not its contents. All warranty claims of any nature are barred if the container has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident.

For complete warranty details, see www.peli.com/warranty


©2016 Pelican Products, S.L.U. All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates. Part. No. 0030-006-900E MAR. 16 www.peli.com

Vonk B.V.
Voorstraat 41 - 3265 BT PIERSHIL
Tel. 088-0330300
info@vonkbv.com
www.vonkbv.com



PELI-HARDIGG™ 33" CLASSIC-V RACK MOUNT CASE

FOR ULTRA FRAGILE EQUIPMENT



- STAINLESS STEEL HANDLES**
Heavy-duty spring loaded handles lay flat, and snap back in place after use
- LOCKING CABLE CATCHES**
Allow for padlock attachment to keep case locked and secure
- HEAVY-DUTY CASTERS**
4 Removable Heavy-Duty Bottom Casters
- 838 mm (33") RACK DEPTH**


SHARED FEATURES

- A: LID HANGER**
Keeps lids attached to case while case is open
- B: MOLDED-IN STACKING RIBS**
Secure non-slip stacking on matched size cases
- C: DOUBLE WALLED RIM FOR TONGUE-IN-GROOVE SEAL**
Remains sealed after impact, splash, rain, air and watertight resistant
- D: POSITIVE ANTI-SHEAR LOCKS**
Prevents lid separation upon impact
- E: BLACK HARDWARE**
Non-reflective black hardware eliminates glare in bright environments
- F: COUPLING CATCHES**
Attaching system for secure stacking
- G: PRESSURE RELEASE VALVE**
Regulates air pressure
- H: COLUMNAR STRENGTH**
Moulded-in ribs provide extra columnar strength
- I: REINFORCED CORNERS AND EDGES**
15% to 20% thicker corners and edges for added impact protection
- J: SHOCK MOUNTS**
Shock mounts provide excellent shock and vibration cushion for delicate equipment
- K: RECESSED HARDWARE**
Hardware protected from impact, and snag free transport
- L: SQUARE HOLE 19" RACK FRAME (WIDTH)**
Fixed square hole frame for universal equipment fit
- M: PATENTED METAL INSERTS**
Catch and hinge attachment points distribute load to case walls

CAT NO.	RACK HEIGHT U SIZE			RACK LENGTH		RACK WIDTH		LID I.D. FRONT/BACK ¹	LENGTH O.D. ²		WIDTH O.D.		HEIGHT O.D. ³		WEIGHT		SHIPPING CUBE	
	U	in	mm	in	mm	in	mm		in	mm	in	mm	in	mm	lbs	kg	ft3	m3
CLASSIC-V-3U	3U	5.25	133	33	838	19	483	2.5 / 5.25	45.8	1163	27.0	686	12.3	311	51.0	23.1	8.8	0.25
CLASSIC-V-4U	4U	7.00	178	33	838	19	483	2.5 / 5.25	45.8	1163	27.0	686	14.6	371	54.0	24.5	10.5	0.30
CLASSIC-V-5U	5U	8.75	222	33	838	19	483	2.5 / 5.25	45.8	1163	27.0	686	16.6	422	56.0	25.4	11.9	0.37
CLASSIC-V-7U	7U	12.25	311	33	838	19	483	2.5 / 5.25	45.8	1163	27.0	686	20.6	504	65.0	29.5	14.7	0.42
CLASSIC-V-9U	9U	15.75	400	33	838	19	483	2.5 / 5.25	45.8	1163	27.0	686	24.3	616	72.0	32.7	17.4	0.49

PELI-HARDIGG™ 24" SUPER-V RACK MOUNT CASE


FOR MODERATELY FRAGILE EQUIPMENT




- COMFORT GRIP PLASTIC HANDLES**
Heavy-duty spring loaded handles lay flat
- 610 mm (24") RACK DEPTH**
- MOLDED IN REAR EDGE CASTERS WITH HANDLES ON THE LID**
For ease of movement

CAT NO.	RACK HEIGHT U SIZE			RACK LENGTH		RACK WIDTH		LID I.D. FRONT/BACK ¹	LENGTH O.D. ²		WIDTH O.D. ³		HEIGHT O.D. ³		WEIGHT		SHIPPING CUBE	
	U	in	mm	in	mm	in	mm		in	mm	in	mm	in	mm	lbs	kg	ft3	m3
SUPER-V-3U	3U	5.25	133	24	610	19	483	2.2 / 5.2	38.5	978	28.3	603	11.4	289	50	22.7	6.0	0.17
SUPER-V-4U	4U	7.00	178	24	610	19	483	2.2 / 5.2	38.5	978	28.3	603	13.1	333	53	24.0	6.9	0.20
SUPER-V-5U	5U	8.75	222	24	610	19	483	2.2 / 5.2	38.5	978	28.3	603	14.9	378	55	24.9	7.9	0.22
SUPER-V-7U	7U	12.25	311	24	610	19	483	2.2 / 5.2	38.5	978	28.3	603	18.4	467	60	27.2	9.7	0.28
SUPER-V-9U	9U	15.75	400	24	610	19	483	2.2 / 5.2	38.5	978	28.3	603	21.9	556	64	29.0	11.6	0.33
SUPER-V-11U	11U	19.25	489	24	610	19	483	2.2 / 5.2	38.5	978	28.3	603	25.4	644	69	31.3	13.4	0.38
SUPER-V-14U	14U	24.50	622	24	610	19	483	2.2 / 5.2	38.5	978	28.3	603	30.6	778	74	33.6	16.2	0.46

PELI-HARDIGG™ 33" CLASSIC-V RACK MOUNT CASES



PELI-HARDIGG™ 24" SUPER-V RACK MOUNT CASES



¹ Lid Outside Dimensions (O.D.) = Lid I.D. plus 31.8 mm (1.25") per lid. ² Length Includes Stacking Ribs. ³ Height Excludes 1" Stacking Ribs (11.2 mm (.44") on Super-V). * Width of all cases includes attached standard handles.