



AEGIS AE12075-40.23

Specifications



Case dimensions

| | | | | | | |
|---------------------|------|---|-----|---|-----|----|
| Internal Dimensions | 1112 | x | 662 | x | 552 | mm |
| External Dimensions | 1200 | x | 750 | x | 630 | mm |

Internal Volume 0.406 m³

Buoyancy In Water 406 Kg

Base dimensions

| | | | | | | |
|---------------------|------|---|-----|---|-----|----|
| Internal Dimensions | 1112 | x | 662 | x | 387 | mm |
| External Dimensions | 1200 | x | 750 | x | 400 | mm |

Lid dimensions

| | | | | | | |
|---------------------|------|---|-----|---|-----|----|
| Internal Dimensions | 1112 | x | 662 | x | 165 | mm |
| External Dimensions | 1200 | x | 750 | x | 230 | mm |

| | |
|-------------------------------|----------------------------------|
| Case Material | Rotomoulded Polyethylene (LLDPE) |
| Latch Material | Blackened Stainless Steel |
| Gasket Material | Silicone Sponge |
| Rivet Material | Stainless Steel |
| Minimum Operating Temperature | -40 °C (-40 °F) |
| Maximum Operating Temperature | +70 °C (+158 °F) |
| Approx. Weight | TBC Kg |

Standard colour range

Aegis Cases are generally provided in Black, Olive Drab or Portland Stone. Subject to availability other standard colours or bespoke colours are available subject to MOQ.



Testing and Approvals:

MIL-STD-810G, STANAG 4280, STANAG 4340, IP67, ATA 300
 Def Stan 81-144, Def Stan 00-035 Part 3, Def Stan 81-041 Part 4.

Dimensional Tolerances +/- 1% of stated dimensions

This case is subject to a minimum order quantity