

A man in a grey t-shirt and dark trousers walks across a tarmac, carrying a professional video camera in his right hand and a tan Peli Protector Case in his left. In the background, a fighter jet is parked on the airfield.

2025 PROTECTOR CASE CATALOGUE



Rugged, uncompromising and trusted, Peli cases protect what matters to you, from the everyday to the extraordinary. Peli Protector Cases are made with copolymer polypropylene and cutting edge technology, which makes them virtually indestructible and resistant to the most extreme conditions. Proven for over 45 years in the most demanding environments.

Guaranteed for Life and sustainable due to its long life.



PROTECTOR CASES

FEATURES	4-5
PRODUCTS	6-27
Micro Cases	6
Small Cases	10
Laptop Cases	14
Medium Cases	16
Large Cases	22
Long Cases	26
SPECIFICATIONS	28-39
ACCESSORIES	40-47
Base Protection	40
Lid Protection	42
Other Accessories	44
Special Applications	46

PROTECTOR CASES



■ STRONGER BY DESIGN

The Peli Protector Case™ uses an open cell core and solid wall construction, which is actually stronger and lighter than a solid core wall. Stainless steel pins are used for hinges and handles.

■ DOUBLE-THROW LATCHES

The Double-Throw latches are smarter and easier to open: it's the classic 'C' clamp design with a secondary movement that works like a pry bar to start the release and offers plenty of leverage to open with a light pull.

■ EASY RIDING

Stainless steel ball bearing wheels (on selected cases) last longer and ride smoother. The nylon hub adjacent to the stainless steel resists heat. Result: less wear and tear on the polyurethane tire.

■ REINFORCED PADLOCK PROTECTORS

Stainless steel reinforced padlock protectors provide added strength and extra security against cutting and theft.

■ WATERTIGHT

The secret is the tongue and groove fit with a polymer o-ring which creates a watertight seal that gives each case its IP67 waterproof rating. Made from neoprene, these gaskets fit securely into a groove in the case lid, ensuring a tight seal when latched.

■ COOL UNDER PRESSURE


The Automatic Pressure Equalisation Valve releases built-up air pressure while keeping water molecules out, resulting in a watertight case that is even easier to open.


* Lifetime guarantee not applicable where prohibited by law.

MICRO CASES

From small sensitive components to smartphones, protect your gear from the elements in a Memory Card Case or Micro Case from Peli.



 **IP67
WATERTIGHT**
Dustproof and waterproof
up to depths of 1 meter
for thirty minutes.

 **IP68
WATERPROOF**
Dustproof and watertight
up to depths of 2 meter for
thirty minutes.

G5 RF FIELD WALLET



INTERNAL DIMS:
1.1 x 6.5 x 10.4 cm
(0.43" x 2.56" x 4.10")
EXTERNAL DIMS:
2 x 7.6 x 12.7 cm
(0.80" x 3.00" x 5.00")
LID/BOTTOM DEPTH:
N/A
WEIGHT:
0.1 kg (0.33 lbs)



1010 MICRO CASE



INTERNAL DIMS:
11.1 x 7.3 x 4.3 cm
(4.37" x 2.87" x 1.68")
EXTERNAL DIMS:
14.9 x 10.3 x 5.4 cm
(5.88" x 4.06" x 2.12")
LID/BOTTOM DEPTH:
1.8 cm / 2.4 cm
(0.69" / 0.94")
WEIGHT:
0.19 kg (0.41 lbs.) WITH FOAM
0.18 kg (0.4 lbs) NO FOAM



0915 SD CARD CASE



INTERNAL DIMS:
12.2 x 5.7 x 1.4 cm
(4.79" x 2.25" x 0.55")
EXTERNAL DIMS:
14.1 x 8.3 x 2.2 cm
(5.55" x 3.27" x 0.85")
LID/BOTTOM DEPTH:
N/A
WEIGHT:
0.1 kg (0.22 lbs) WITH LINER



Stores 12 SD cards, 6 mini SD cards
and 6 micro SD cards (not included)



0965 SD CARD CASE



INTERNAL DIMS:
12.2 x 5.7 x 1.4 cm
(4.79" x 2.25" x 0.55")
EXTERNAL DIMS:
14.1 x 8.3 x 2.2 cm
(5.55" x 3.27" x 0.85")
LID/BOTTOM DEPTH:
N/A
WEIGHT:
0.1 kg (0.22 lbs)



Stores XQD and CFexpress cards
(not included)



Photo by Alvaro Sanz

*These colours are available upon minimum quantities, as well as other configurations.
Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED



1030 MICRO CASE



INTERNAL DIMS:
16.2 x 6.7 x 5.2 cm
(6.37" x 2.62" x 2.06")

EXTERNAL DIMS:
19.1 x 9.8 x 6.2 cm
(7.50" x 3.87" x 2.43")

LID/BOTTOM DEPTH:
1.8 cm / 3.2 cm
(0.69" / 1.25")

WEIGHT:
0.28 kg (0.61 lbs) WITH FOAM
0.27 kg (0.6 lbs) NO FOAM



1040 MICRO CASE



INTERNAL DIMS:
16.5 x 9.8 x 4.4 cm
(6.50" x 3.87" x 1.75")

EXTERNAL DIMS:
19.1 x 12.9 x 5.4 cm
(7.50" x 5.06" x 2.12")

LID/BOTTOM DEPTH:
1.8 cm / 2.4 cm
(0.69" / 0.94")

WEIGHT:
0.32 kg (0.71 lbs) WITH FOAM
0.32 kg (0.7 lbs) NO FOAM



1015 MICRO CASE



INTERNAL DIMS:
13.1 x 6.7 x 3.5 cm
(5.14" x 2.64" x 1.37")

EXTERNAL DIMS:
17 x 9.9 x 4.7 cm
(6.68" x 3.88" x 1.86")

LID/BOTTOM DEPTH:
1.1 cm / 2.4 cm
(0.43" / 0.94")

WEIGHT:
0.21 kg (0.46 lbs)



1020 MICRO CASE



INTERNAL DIMS:
13.5 x 9 x 4.3 cm
(5.31" x 3.56" x 1.68")

EXTERNAL DIMS:
17.3 x 12.1 x 5.4 cm
(6.82" x 4.75" x 2.12")

LID/BOTTOM DEPTH:
1.8 cm / 2.4 cm
(0.69" / 0.94")

WEIGHT:
0.25 kg (0.56 lbs) WITH FOAM
0.25 kg (0.55 lbs) NO FOAM



R20 RUCK CASE



INTERNAL DIMS:
18 x 8.6 x 5 cm
(7.07" x 3.39" x 1.95")

EXTERNAL DIMS:
22.8 x 12.3 x 7.3 cm
(8.96" x 4.83" x 2.88")

LID/BOTTOM DEPTH:
N/A

WEIGHT:
0.6 kg (1.26 lbs)



M50 MICRO CASE



INTERNAL DIMS:
18.5 x 10.9 x 6.1 cm
(7.30" x 4.30" x 2.40")

EXTERNAL DIMS:
20.6 x 14.0 x 7.4 cm
(8.10" x 5.50" x 2.90")

LID/BOTTOM DEPTH:
2 cm / 4.4 cm
(0.80" / 1.73")

WEIGHT:
0.4 kg (0.85 lbs)



M40 MICRO CASE



INTERNAL DIMS:
15.2 x 9.7 x 5.3 cm
(6.00" x 3.80" x 2.10")

EXTERNAL DIMS:
17.3 x 12.7 x 6.6 cm
(6.80" x 5.00" x 2.60")

LID/BOTTOM DEPTH:
2 cm / 3.6 cm
(0.80" / 1.40")

WEIGHT:
0.3 kg (0.65 lbs)



1050 MICRO CASE



INTERNAL DIMS:
16 x 9.3 x 7 cm
(6.31" x 3.68" x 2.75")

EXTERNAL DIMS:
20.3 x 12.9 x 7.9 cm
(7.99" x 5.06" x 3.12")

LID/BOTTOM DEPTH:
1.8 cm / 4.9 cm
(0.69" / 1.94")

WEIGHT:
0.38 kg (0.83 lbs) WITH FOAM
0.37 kg (0.81 lbs) NO FOAM



PROTECTOR



IP67
WATERTIGHT

Dustproof and waterproof up to depths of 1 meter for thirty minutes.



IP68
WATERPROOF

Dustproof and watertight up to depths of 2 meter for thirty minutes.

ICONOGRAPHY

*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

SMALL CASES

Lightweight, but extremely strong; compact, yet fully capable. Perfect for valuable gear like hand tools and small to medium electronic components, hand held GPS systems, and DSLR cameras. All small cases are available empty or with pre-scored Pick N Pluck™ foam.



Note that the dimensions of some cases manufactured in Germany differ slightly from the equivalent cases manufactured in the US. Please review the case dimensions carefully before initiating any project.

SEE ALL



**IP67
WATERTIGHT**

Dustproof and waterproof up to depths of 1 meter for thirty minutes.



**IP68
WATERPROOF**

Dustproof and watertight up to depths of 2 meter for thirty minutes.



**PANEL
FRAME**

This case can be adapted for use with an electronic interface panel.

Photo by Ebru Survivor



1120



INTERNAL DIMS:
18.5 x 12.1 x 8.5 cm
(7.29" x 4.78" x 3.33")

EXTERNAL DIMS:
21.4 x 17.2 x 9.8 cm
(8.41" x 6.76" x 3.87")

LID/BOTTOM DEPTH:
1.3 cm / 6.5 cm
(0.50" / 2.56")

WEIGHT:
0.65 kg (1.43 lbs) WITH FOAM
0.61 kg (1.34 lbs) NO FOAM



R40 RUCK CASE



INTERNAL DIMS:
19.4 x 11.9 x 4.8 cm
(7.63" x 4.70" x 1.90")

EXTERNAL DIMS:
25 x 15.5 x 7.3 cm
(9.84" x 6.12" x 2.89")

LID/BOTTOM DEPTH:
N/A

WEIGHT:
0.8 kg (1.68 lbs)



1060 MICRO CASE



INTERNAL DIMS:
21 x 10.8 x 5.7 cm
(8.25" x 4.25" x 2.25")

EXTERNAL DIMS:
25.1 x 14.2 x 6.7 cm
(9.88" x 5.59" x 2.63")

LID/BOTTOM DEPTH:
1.8 cm / 3.7 cm
(0.69" / 1.44")

WEIGHT:
0.47 kg (1.03 lbs) WITH FOAM
0.45 kg (1 lbs) NO FOAM



1150



INTERNAL DIMS:
21.1 x 14.7 x 9.5 cm
(8.29" x 5.79" x 3.75")

EXTERNAL DIMS:
24 x 19.8 x 10.9 cm
(9.44" x 7.80" x 4.29")

LID/BOTTOM DEPTH:
1.9 cm / 7.3 cm
(0.75" / 2.87")

WEIGHT:
0.79 kg (1.75 lbs) WITH FOAM
0.73 kg (1.61 lbs) NO FOAM



*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED



M60 MICRO CASE



INTERNAL DIMS:
21.6 x 10.9 x 6.9 cm
(8.50" x 4.30" x 2.70")

EXTERNAL DIMS:
23.6 x 15.2 x 8.1 cm
(9.30" x 6.00" x 3.20")

LID/BOTTOM DEPTH:
2 cm / 5.1 cm
(0.80" / 2.01")

WEIGHT:
0.5 kg (1.05 lbs)



R60 RUCK CASE



INTERNAL DIMS:
22.6 x 13.6 x 7.5 cm
(6.37" x 2.62" x 2.06")

EXTERNAL DIMS:
28.3 x 17.4 x 9.9 cm
(7.50" x 3.87" x 2.43")

LID/BOTTOM DEPTH:
N/A

WEIGHT:
1.1 kg (2.34 lbs)



1300



INTERNAL DIMS:
23.3 x 17.8 x 15.6 cm
(9.17" x 7.00" x 6.12")

EXTERNAL DIMS:
27.2 x 24.8 x 17.5 cm
(10.62" x 9.68" x 6.87")

LID/BOTTOM DEPTH:
3 cm / 12.6 cm
(1.18" / 6.11")

WEIGHT:
1.6 kg (3.53 lbs) WITH FOAM
1.4 kg (3.09 lbs) NO FOAM



1200



INTERNAL DIMS:
23.6 x 18.1 x 10.5 cm
(9.31" x 7.13" x 4.12")

EXTERNAL DIMS:
27.1 x 24.8 x 12.3 cm
(10.67" x 9.75" x 4.86")

LID/BOTTOM DEPTH:
3 cm / 7.4 cm
(1.19" / 2.93")

WEIGHT:
1.2 kg (2.75 lbs) WITH FOAM
1.2 kg (2.55 lbs) NO FOAM



CASE CONTENTS NOT INCLUDED

1170



INTERNAL DIMS:
26.8 x 15.3 x 8 cm
(10.54" x 6.04" x 3.16")

EXTERNAL DIMS:
29.6 x 21.2 x 9.6 cm
(11.64" x 8.34" x 3.78")

LID/BOTTOM DEPTH:
2.7 cm / 5.3 cm
(1.08" / 2.08")

WEIGHT:
0.95 kg (2.1 lbs) WITH FOAM
0.89 kg (1.96 lbs) NO FOAM



1400



INTERNAL DIMS:
30 x 22.5 x 13.2 cm
(11.81" x 8.87" x 5.18")


EXTERNAL DIMS:
34 x 29.5 x 15.2 cm
(13.37" x 11.62" x 6.00")

LID/BOTTOM DEPTH:
3 cm / 10.2 cm
(1.18" / 4.00")

WEIGHT:
2 kg (4.41 lbs) WITH FOAM
1.8 kg (3.97 lbs) NO FOAM



PROTECTOR



**IP67
WATERTIGHT**

Dustproof and waterproof up to depths of 1 meter for thirty minutes.



**IP68
WATERPROOF**

Dustproof and watertight up to depths of 2 meter for thirty minutes.



**PANEL
FRAME**

This case can be adapted for use with an electronic interface panel.

ICONOGRAPHY

*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED


LAPTOP CASES

The Peli line of tablet and laptop cases feature revolutionary design, construction and durability. Peli HardBack™ cases are available in many sizes and insert options. Moulded plush shock absorbing liner protects from impact and won't scratch your device— superior protection for your office on the go!



Note that the dimensions of some cases manufactured in Germany differ slightly from the equivalent cases manufactured in the US. Please review the case dimensions carefully before initiating any project.

SEE ALL



Dustproof and waterproof up to depths of 1 meter for thirty minutes.



This case can be adapted for use with an electronic interface panel.



Quiet rolling stainless-steel bearing wheels.

1430 TOP LOADER CASE



INTERNAL DIMS:

34.4 x 14.6 x 29.7 cm
(13.56" x 5.76" x 11.7")

EXTERNAL DIMS:

41.7 x 22.1 x 33.4 cm
(16.40" x 8.71" x 13.15")

LID/BOTTOM DEPTH:

5.1 cm / 24.6 cm
(2.00" / 9.70")

WEIGHT:

2.95 kg (6.5 lbs) WITH FOAM
2.54 kg (5.6 lbs) NO FOAM



1440 TOP LOADER CASE



INTERNAL DIMS:

43.4 x 19.1 x 40.6 cm
(17.10" x 7.50" x 16.00")

EXTERNAL DIMS:

50 x 30.5 x 45.7 cm
(19.70" x 12.00" x 18.00")

LID/BOTTOM DEPTH:

5.1 cm / 35.6 cm
(2.00" / 14.00")

WEIGHT:

7.48 kg (16.5 lbs) WITH FOAM
6.58 kg (14.5 lbs) NO FOAM



1490CC1



INTERNAL DIMS:

45.1 x 28.9 x 10.5 cm
(17.75" x 11.37" x 4.12")

EXTERNAL DIMS:

50.5 x 35.4 x 11.9 cm
(19.87" x 13.93" x 4.68")

LID/BOTTOM DEPTH:

3.8 cm / 6.7 cm
(1.50" / 2.62")

WEIGHT:

2.9 kg (6.50 lbs) WITH FOAM
2.5 kg (5.47 lbs) NO FOAM



1495CC1



INTERNAL DIMS:

47.9 x 33.3 x 9.7 cm
(18.87" x 13.12" x 3.81")

EXTERNAL DIMS:

54.9 x 43.8 x 12.4 cm
(21.62" x 17.25" x 4.87")

LID/BOTTOM DEPTH:

2.8 cm / 6.8 cm
(1.12" / 2.68")

WEIGHT:

3.8 kg (8.37 lbs) WITH FOAM
3.3 kg (7.23 lbs) NO FOAM



1470



INTERNAL DIMS:

39.9 x 27.2 x 9.8 cm
(15.70" x 10.70" x 3.87")

EXTERNAL DIMS:

42.9 x 33.6 x 11.4 cm
(16.88" x 13.23" x 4.47")

LID/BOTTOM DEPTH:

3.7 cm / 6.1 cm
(1.47" / 2.40")

WEIGHT:

2.5 kg (5.51 lbs) WITH FOAM
1.94 kg (4.28 lbs) NO FOAM



1490



INTERNAL DIMS:

45.1 x 28.9 x 10.5 cm
(17.75" x 11.37" x 4.12")

EXTERNAL DIMS:

50.5 x 35.4 x 11.9 cm
(19.87" x 13.93" x 4.68")

LID/BOTTOM DEPTH:

3.8 cm / 6.7 cm
(1.50" / 2.62")

WEIGHT:

2.95 kg (6.5 lbs) WITH FOAM
2.48 kg (5.47 lbs) NO FOAM



1495



INTERNAL DIMS:

47.9 x 33.3 x 9.7 cm
(18.87" x 13.12" x 3.81")

EXTERNAL DIMS:

54.9 x 43.8 x 12.4 cm
(21.62" x 17.25" x 4.87")

LID/BOTTOM DEPTH:

2.8 cm / 6.8 cm
(1.12" / 2.68")

WEIGHT:

3.8 kg (8.37 lbs) WITH FOAM
3.28 kg (7.23 lbs) NO FOAM



*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED

MEDIUM CASES

Mobility with room for protecting larger gear or multiple instruments and accessories. Interior options are available for extra protection. Selected models meet carry-on luggage specifications. Most cases are available empty, with foam, TrekPak™ or padded dividers.



Note that the dimensions of some cases manufactured in Germany differ slightly from the equivalent cases manufactured in the US. Please review the case dimensions carefully before initiating any project.

SEE ALL



**IP67
WATERTIGHT**

Dustproof and waterproof up to depths of 1 meter for thirty minutes.



**PANEL
FRAME**

This case can be adapted for use with an electronic interface panel.



**WHEELED
CASE**

Quiet rolling stainless-steel bearing wheels.

1450



INTERNAL DIMS:
37.2 x 26 x 15.5 cm
(14.66" x 10.24" x 6.12")

EXTERNAL DIMS:
41.8 x 33 x 17.3 cm
(16.44" x 13.00" x 6.82")

LID/BOTTOM DEPTH:
4.4 cm / 11.1 cm
(1.75" / 4.37")

WEIGHT:
2.9 kg (6.39 lbs) WITH FOAM
2.5 kg (5.51 lbs) NO FOAM



1500



INTERNAL DIMS:
42.5 x 28.4 x 15.5 cm
(16.75" x 11.18" x 6.12")

EXTERNAL DIMS:
47 x 35.7 x 17.6 cm
(18.50" x 14.06" x 6.93")

LID/BOTTOM DEPTH:
4.6 cm / 10.9 cm
(1.81" / 4.31")

WEIGHT:
3.6 kg (7.94 lbs) WITH FOAM
3.2 kg (7.13 lbs) NO FOAM



0340



INTERNAL DIMS:
45.7 x 45.7 x 45.7 cm
(18.00" x 18.00" x 18.00")

EXTERNAL DIMS:
52.1 x 52.1 x 48.9 cm
(20.50" x 20.50" x 19.25")

LID/BOTTOM DEPTH:
11.4 cm / 34.3 cm
(4.50" / 13.50")

WEIGHT:
13.5 kg (29.76 lbs) WITH FOAM
10.89 kg (24 lbs) NO FOAM



Caster wheels included

1520



INTERNAL DIMS:
45.9 x 32.7 x 17.1 cm
(18.06" x 12.89" x 6.72")

EXTERNAL DIMS:
50.2 x 40.1 x 18.8 cm
(19.78" x 15.77" x 7.41")

LID/BOTTOM DEPTH:
4.5 cm / 12.5 cm
(1.79" / 4.93")

WEIGHT:
4.24 kg (9.35 lbs) WITH FOAM
3.76 kg (8.29 lbs) NO FOAM



*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED



1460 TOOL CASE



INTERNAL DIMS:
47.1 x 25.2 x 27.7cm
(18.54" x 9.92" x 10.92")

EXTERNAL DIMS:
53 x 32.3 x 32.4 cm
(20.85" x 12.73" x 12.75")

LID/BOTTOM DEPTH:
12.5 cm / 15.3 cm
(4.91" / 6.01")

WEIGHT:
5.9 kg (13 lbs) WITH TRAY ASSEMBLY



1550



INTERNAL DIMS:
47.3 x 36 x 19.6 cm
(18.63" x 14.18" x 7.72")

EXTERNAL DIMS:
52.5 x 43.7 x 21.3 cm
(20.66" x 17.20" x 8.40")

LID/BOTTOM DEPTH:
4.4 cm / 14.9 cm
(1.75" / 5.87")

WEIGHT:
5.4 kg (11.90 lbs) WITH FOAM
4.8 kg (10.58 lbs) NO FOAM



1510



INTERNAL DIMS:
50.2 x 27.9 x 19.3 cm
(19.75" x 11.00" x 7.60")

EXTERNAL DIMS:
55.9 x 35.1 x 22.9 cm
(22.00" x 13.81" x 9.00")

LID/BOTTOM DEPTH:
4.5 cm / 14.7 cm
(1.79" / 5.79")

WEIGHT:
6.2 kg (13.60 lbs) WITH FOAM
5.4 kg (11.99 lbs) NO FOAM



1460



INTERNAL DIMS:
47.1 x 25.2 x 27.7cm
(18.54" x 9.92" x 10.92")

EXTERNAL DIMS:
53 x 32.3 x 32.4 cm
(20.85" x 12.73" x 12.75")

LID/BOTTOM DEPTH:
12.5 cm / 15.3 cm
(4.91" / 6.01")

WEIGHT:
5.66 kg (12.48 lbs) WITH FOAM
3.97 kg (8.75 lbs) NO FOAM



1460 EMS CASE**



INTERNAL DIMS:
47.1 x 25.2 x 27.7 cm
(18.54" x 9.92" x 10.92")

EXTERNAL DIMS:
53 x 32.3 x 32.4 cm
(20.85" x 12.73" x 12.75")

LID/BOTTOM DEPTH:
12.5 cm / 15.3 cm
(4.91" / 6.01")

WEIGHT:
8.26 kg (18.2 lbs)
WITH TRAY ASSEMBLY



CASE CONTENTS NOT INCLUDED

PROTECTOR



**IP67
WATERTIGHT**

Dustproof and waterproof up to
depths of 1 meter for thirty minutes.



**PANEL
FRAME**

This case can be adapted for use
with an electronic interface panel.



**WHEELED
CASE**

Quiet rolling stainless-steel
bearing wheels.

ICONOGRAPHY

*These colours are available upon minimum quantities, as well as other configurations.
Check with your Customer Service representative for further details.
** This case is only available upon minimum order quantities. (1460EMS).

*These colours are available upon minimum quantities, as well as other configurations.
Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED



Photo by Samuel Gardenas

1510M



INTERNAL DIMS:
50.2 x 27.9 x 19.3 cm
(19.75" x 11.00" x 7.60")

EXTERNAL DIMS:
59.8 x 36.5 x 27 cm
(23.55" x 14.36" x 10.62")

LID/BOTTOM DEPTH:
4.5 cm / 14.7 cm
(1.79" / 5.79")

WEIGHT:
8.1 kg (17.91 lbs) WITH FOAM
7.4 kg (16.3 lbs) NO FOAM



1510SC



INTERNAL DIMS:
50.2 x 27.9 x 19.3 cm
(19.75" x 11.00" x 7.60")

EXTERNAL DIMS:
55.9 x 35.1 x 22.9 cm
(22.00" x 13.81" x 9.00")

LID/BOTTOM DEPTH:
4.5 cm / 14.7 cm
(1.79" / 5.79")

WEIGHT:
6.2 kg (13.6 lbs) WITH FOAM
5.4 kg (11.99 lbs) NO FOAM



1510LOC



INTERNAL DIMS:
50.2 x 27.9 x 19.3 cm
(19.75" x 11.00" x 7.60")

EXTERNAL DIMS:
55.9 x 35.1 x 22.9 cm
(22.00" x 13.81" x 9.00")

LID/BOTTOM DEPTH:
4.5 cm / 14.7 cm
(1.79" / 5.79")

WEIGHT:
6.2 kg (13.6 lbs) WITH FOAM
5.4 kg (11.99 lbs) NO FOAM



1510LFC



INTERNAL DIMS:
50.2 x 27.9 x 19.3 cm
(19.75" x 11.00" x 7.60")

EXTERNAL DIMS:
55.9 x 35.1 x 22.9 cm
(22.00" x 13.81" x 9.00")

LID/BOTTOM DEPTH:
4.5 cm / 14.7 cm
(1.79" / 5.79")

WEIGHT:
6.2 kg (13.6 lbs) WITH FOAM
5.4 kg (11.99 lbs) NO FOAM



CASE CONTENTS NOT INCLUDED

1560



INTERNAL DIMS:
50.6 x 38 x 22.9 cm
(19.92" x 14.98" x 9.00")

EXTERNAL DIMS:
56.1 x 45.5 x 26.5 cm
(22.07" x 17.92" x 10.42")

LID/BOTTOM DEPTH:
5.1 cm / 17.8 cm
(2.00" / 7.00")

WEIGHT:
9.1 kg (20.00 lbs) WITH FOAM
7.7 kg (17.00 lbs) NO FOAM



1560SC



INTERNAL DIMS:
50.6 x 38 x 22.9 cm
(19.92" x 14.98" x 9.00")

EXTERNAL DIMS:
56.1 x 45.5 x 26.5 cm
(22.07" x 17.92" x 10.42")

LID/BOTTOM DEPTH:
5.1 cm / 17.8 cm
(2.00" / 7.00")

WEIGHT:
8.2 kg (18.18 lbs) WITH FOAM
7.7 kg (17 lbs) NO FOAM



1560LFC



INTERNAL DIMS:
50.6 x 38 x 22.9 cm
(19.92" x 14.98" x 9.00")

EXTERNAL DIMS:
56.1 x 45.5 x 26.5 cm
(22.07" x 17.92" x 10.42")

LID/BOTTOM DEPTH:
5.1 cm / 17.8 cm
(2.00" / 7.00")

WEIGHT:
8.2 kg (18.18 lbs) WITH FOAM
7.7 kg (17 lbs) NO FOAM



1560M



INTERNAL DIMS:
50.6 x 38 x 22.9 cm
(19.92" x 14.98" x 9.00")

EXTERNAL DIMS:
60.4 x 46.6 x 30.7 cm
(23.78" x 18.33" x 12.08")

LID/BOTTOM DEPTH:
5.1 cm / 17.8 cm
(2.00" / 7.00")

WEIGHT:
11 kg (24.3 lbs) WITH FOAM
9.7 kg (21.3 lbs) NO FOAM



1560LOC



INTERNAL DIMS:
50.6 x 38 x 22.9 cm
(19.92" x 14.98" x 9.00")

EXTERNAL DIMS:
56.1 x 45.5 x 26.5 cm
(22.07" x 17.92" x 10.42")

LID/BOTTOM DEPTH:
5.1 cm / 17.8 cm
(2.00" / 7.00")

WEIGHT:
8.2 kg (18.18 lbs) WITH FOAM
7.7 kg (17 lbs) NO FOAM



0350



INTERNAL DIMS:
50.8 x 50.8 x 50.8 cm
(2.00" x 2.00" x 2.00")

EXTERNAL DIMS:
57.2 x 57 x 54 cm
(22.50" x 22.43" x 21.25")

LID/BOTTOM DEPTH:
12.7 cm / 38.1 cm
(5.00" / 15.00")

WEIGHT:
14.52 kg (32.01 lbs) WITH FOAM
11.79 kg (25.99 lbs) NO FOAM



ICONOGRAPHY

PROTECTOR

 **IP67
WATERTIGHT**
Dustproof and waterproof up to
depths of 1 meter for thirty minutes.

 **PANEL
FRAME**
This case can be adapted for use
with an electronic interface panel.

 **WHEELED
CASE**
Quiet rolling stainless-steel
bearing wheels.

*These colours are available upon minimum quantities, as well as other configurations.
Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED

20 PELI PROTECTOR CASE CATALOGUE

For the most up-to-date information, please visit www.peli.com

For the most up-to-date information, please visit www.peli.com

PELI PROTECTOR CASE CATALOGUE 21

LARGE CASES

Designed for extreme protection during transport and storage. Customisable interiors allow for extra protection and inventory control. Selected models feature retractable handles, extra wide grips and sturdy casters for efficient mobility.



Note that the dimensions of some cases manufactured in Germany differ slightly from the equivalent cases manufactured in the US. Please review the case dimensions carefully before initiating any project.



**IP67
WATERTIGHT**
Dustproof and waterproof
up to depths of 1 meter
for thirty minutes.

**WHEELED
CASE**
Quiet rolling stainless-steel
bearing wheels.

0450



INTERNAL DIMS:
Varies by drawer
configuration
EXTERNAL DIMS:
60.8 x 37.5 x 45.6 cm
(23.95" x 14.75" x 17.95")
LID/BOTTOM DEPTH:
N/A
WEIGHT:
21.95 kg (48.4 lbs)



1620



INTERNAL DIMS:
54.3 x 41.4 x 31.9 cm
(21.37" x 16.31" x 12.56")
EXTERNAL DIMS:
63 x 49.2 x 35.2 cm
(24.81" x 19.37" x 13.87")
LID/BOTTOM DEPTH:
5.2 cm / 26.7 cm
(2.06" / 10.50")
WEIGHT:
11.8 kg (26.01 lbs) WITH FOAM
11.1 kg (24.47 lbs) NO FOAM



1620M



INTERNAL DIMS:
54.6 x 41.7 x 31.9 cm
(21.48" x 16.42" x 12.54")
EXTERNAL DIMS:
66.5 x 58.4 x 39.6 cm
(26.2" x 23.00" x 15.61")
LID/BOTTOM DEPTH:
5.1 cm / 26.7 cm
(2.01" / 10.53")
WEIGHT:
14.3 kg (31.42 lbs) WITH FOAM
12.7 kg (28 lbs) NO FOAM



1600



INTERNAL DIMS:
54.6 x 42 x 20.2 cm
(21.51" x 16.54" x 7.95")
EXTERNAL DIMS:
61.8 x 49.4 x 22.2 cm
(24.35" x 19.46" x 8.75")
LID/BOTTOM DEPTH:
4.4 cm / 15.5 cm
(1.75" / 6.12")
WEIGHT:
6.4 kg (14.11 lbs) WITH FOAM
5.9 kg (13 lbs) NO FOAM



Photo by David Ochoa

*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED



1610



INTERNAL DIMS:

55.1 x 42.2 x 26.8 cm
(21.68" x 16.62" x 10.56")

EXTERNAL DIMS:

62.8 x 49.7 x 30.3 cm
(24.71" x 19.58" x 11.93")

LID/BOTTOM DEPTH:

5.2 cm / 21.6 cm
(2.06" / 8.50")

WEIGHT:

10.2 kg (22.49 lbs) WITH FOAM
9.1 kg (20 lbs) NO FOAM



1640



INTERNAL DIMS:

60.2 x 61 x 35.3 cm
(23.70" x 24.00" x 13.90")

EXTERNAL DIMS:

69.1 x 69.9 x 41.4 cm
(27.20" x 27.50" x 16.30")

LID/BOTTOM DEPTH:

5.1 cm / 30.2 cm
(2.00" / 11.90")

WEIGHT:

17.24 kg (38 lbs) WITH FOAM
15.42 kg (34 lbs) NO FOAM



1610M



INTERNAL DIMS:

55.3 x 42.4 x 27 cm
(21.78" x 16.69" x 10.62")

EXTERNAL DIMS:

66.5 x 58.4 x 34.7 cm
(26.20" x 23.00" x 13.68")

LID/BOTTOM DEPTH:

5.2 cm / 21.8 cm
(2.05" / 8.57")

WEIGHT:

13.2 kg (29.1 lbs) WITH FOAM
11.9 kg (26.3 lbs) NO FOAM



0370



INTERNAL DIMS:

61 x 61 x 61 cm
(24.00" x 24.00" x 24.00")

EXTERNAL DIMS:

67.3 x 67.3 x 64.1 cm
(26.50" x 26.50" x 25.25")

LID/BOTTOM DEPTH:

12.7 cm / 48.3 cm
(5.00" / 19.00")

WEIGHT:

18.6 kg (41 lbs) WITH FOAM
14.5 kg (31.97 lbs) NO FOAM



1630



INTERNAL DIMS:

70.4 x 53.3 x 39.4 cm
(27.70" x 20.98" x 15.50")

EXTERNAL DIMS:

79.5 x 61.5 x 44.4 cm
(31.28" x 24.21" x 17.48")

LID/BOTTOM DEPTH:

8.3 cm / 30.8 cm
(3.25" / 12.14")

WEIGHT:

16.33 kg (36 lbs) WITH FOAM
14.06 kg (31 lbs) NO FOAM



1670



INTERNAL DIMS:

71.4 x 41.9 x 23.3 cm
(28.10" x 16.49" x 9.19")

EXTERNAL DIMS:

78.8 x 49.3 x 28.4 cm
(31.04" x 19.39" x 11.17")

LID/BOTTOM DEPTH:

4.6 cm / 18.8 cm
(1.80" / 7.39")

WEIGHT:

11.8 kg (26 lbs) WITH FOAM
10.4 kg (23 lbs) NO FOAM



1650



INTERNAL DIMS:

72.2 x 44.2 x 27 cm
(28.41" x 17.40" x 10.64")

EXTERNAL DIMS:

80.1 x 52.1 x 31.7 cm
(31.55" x 20.51" x 12.47")

LID/BOTTOM DEPTH:

4.6 cm / 22.5 cm
(1.81" / 8.84")

WEIGHT:

12.73 kg (28.06 lbs) WITH FOAM
10.9 kg (24.03 lbs) NO FOAM



1730



INTERNAL DIMS:

86.4 x 61 x 31.8 cm
(34.00" x 24.00" x 12.50")

EXTERNAL DIMS:

95.3 x 68.9 x 36.5 cm
(37.50" x 27.13" x 14.37")

LID/BOTTOM DEPTH:

6.4 cm / 25.4 cm
(2.50" / 1.00")

WEIGHT:

17.24 kg (38 lbs) WITH FOAM
13.61 kg (30 lbs) NO FOAM



1660



INTERNAL DIMS:

71.6 x 50.2 x 44.8 cm
(28.18" x 19.75" x 17.62")

EXTERNAL DIMS:

80 x 58.1 x 48.3 cm
(31.50" x 22.87" x 19.00")

LID/BOTTOM DEPTH:

8.9 cm / 35.9 cm
(3.50" / 14.12")

WEIGHT:

19.1 kg (42.11 lbs) WITH FOAM
15.5 kg (34.17 lbs) NO FOAM



1690



INTERNAL DIMS:

76.5 x 63.8 x 39 cm
(30.13" x 25.13" x 15.36")

EXTERNAL DIMS:

84.9 x 72.1 x 44.8 cm
(33.43" x 28.40" x 17.65")

LID/BOTTOM DEPTH:

7.3 cm / 30.8 cm
(2.86" / 12.14")

WEIGHT:

19.5 kg (43 lbs) WITH FOAM
15.42 kg (34 lbs) NO FOAM



0500

INTERNAL DIMS:

88.8 x 46.9 x 64.1 cm
(34.95" x 18.45" x 25.25")

EXTERNAL DIMS:

101.5 x 59.6 x 72.8 cm
(39.95" x 23.45" x 28.65")

LID/BOTTOM DEPTH:

5.7 cm / 58.4 cm
(2.25" / 23.00")

WEIGHT:

26.58 kg (58.6 lbs) WITH FOAM
22.68 kg (50 lbs) NO FOAM



PROTECTOR



IP67
WATERTIGHT

Dustproof and waterproof up to depths of 1 meter for thirty minutes.



WHEELED
CASE

Quiet rolling stainless-steel bearing wheels.

ICONOGRAPHY

*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

LONG CASES

Ideal for weapons, but also used by industrial workers for instruments and gear. Equipped with sturdy polyurethane wheels for ease of transport.



Note that the dimensions of some cases manufactured in Germany differ slightly from the equivalent cases manufactured in the US. Please review the case dimensions carefully before initiating any project.

SEE ALL



IP67
WATERTIGHT

Dustproof and waterproof up to depths of 1 meter for thirty minutes.



WHEELED
CASE

Quiet rolling stainless-steel bearing wheels.

1700



INTERNAL DIMS:
90.8 x 34.3 x 13.3 cm
(35.75" x 13.50" x 5.25")

EXTERNAL DIMS:
96.8 x 40.6 x 15.5 cm
(38.12" x 16.00" x 6.12")

LID/BOTTOM DEPTH:
4.4 cm / 8.9 cm
(1.75" / 3.50")

WEIGHT:
7.7 kg (16.98 lbs) WITH FOAM
6.64 kg (16.09 lbs) NO FOAM



1740



INTERNAL DIMS:
104.1 x 32.8 x 30.8 cm
(40.98" x 12.92" x 12.13")

EXTERNAL DIMS:
112.2 x 40.9 x 35.6 cm
(44.16" x 16.09" x 14.00")

LID/BOTTOM DEPTH:
6.5 cm / 24.3 cm
(2.56" / 9.57")

WEIGHT:
12.25 kg (27 lbs) WITH FOAM
9.98 kg (22 lbs) NO FOAM



1720



INTERNAL DIMS:
106.2 x 34.5 x 13.5 cm
(41.80" x 13.58" x 5.33")

EXTERNAL DIMS:
113 x 40.8 x 15.9 cm
(44.48" x 16.07" x 6.25")

LID/BOTTOM DEPTH:
4.4 cm / 8.9 cm
(1.75" / 3.50")

WEIGHT:
10.5 kg (23.10 lbs) WITH FOAM
8.3 kg (18.25 lbs) NO FOAM



1750



INTERNAL DIMS:
128.3 x 34.3 x 13.3 cm
(50.50" x 13.50" x 5.25")

EXTERNAL DIMS:
134.6 x 40.6 x 15.5 cm
(53.00" x 16.00" x 6.12")

LID/BOTTOM DEPTH:
4.4 cm / 8.9 cm
(1.75" / 3.50")

WEIGHT:
11.6 kg (25.57 lbs) WITH FOAM
10.7 kg (23.59 lbs) NO FOAM



1780



INTERNAL DIMS:
104.4 x 54.7 x 37.8 cm
(41.12" x 21.54" x 14.88")

EXTERNAL DIMS:
114 x 64.3 x 41.9 cm
(44.90" x 25.32" x 16.50")

LID/BOTTOM DEPTH:
19.3 cm / 18.5 cm
(7.58" / 7.30")

WEIGHT:
22.2 kg (49 lbs) WITH FOAM
17.4 kg (38.4 lbs) NO FOAM



0550



INTERNAL DIMS:
120.8 x 61.1 x 44.9 cm
(47.57" x 24.07" x 17.68")

EXTERNAL DIMS:
129.7 x 70 x 57.9 cm
(51.05" x 27.54" x 22.79")

LID/BOTTOM DEPTH:
8.1 cm / 36.8 cm
(3.19" / 14.49")

WEIGHT:
43.09 kg (95 lbs) WITH FOAM
35.92 kg (79.2 lbs) NO FOAM



shown with optional
caster wheels

1770



INTERNAL DIMS:
138.6 x 39.6 x 21.9 cm
(54.58" x 15.58" x 8.63")

EXTERNAL DIMS:
145.8 x 46.9 x 28.5 cm
(57.42" x 18.48" x 11.23")

LID/BOTTOM DEPTH:
4.8 cm / 17.1 cm
(1.88" / 6.75")













WEIGHT:
18.8 kg (41.49 lbs) WITH FOAM
16.3 kg (36.01 lbs) NO FOAM



*These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

CASE CONTENTS NOT INCLUDED

MICRO CASES











CAT. NO.	INTERIOR DIMENSIONS	EXTERIOR DIMENSIONS	LID DEPTH	BOTTOM DEPTH	WEIGHT WITH FOAM	WEIGHT WITHOUT FOAM	BUOYANCY MAXIMUM	TEMPERATURE RANGE (Min/Max)	CERTIFICATES	COLOURS	CAT. NO.
G5 RF Field Wallet	1.1 x 6.5 x 10.4 cm	2 x 7.6 x 12.7 cm	N/A	N/A	N/A	0.1 kg	N/A	N/A	IP67		G5 RF Field Wallet
1010	11.1 x 7.3 x 4.3 cm	14.9 x 10.3 x 5.4 cm	1.8 cm	2.4 cm	0.19 kg	0.18 kg	0.23 kg	-23 / 93° C	IP67		1010
0915	12.2 x 5.7 x 1.4 cm	14.1 x 8.3 x 2.2 cm	N/A	N/A	0.1 kg	N/A	N/A	N/A	IPx4		0915
0965	12.2 x 5.7 x 1.4 cm	14.1 x 8.3 x 2.2 cm	N/A	N/A	0.1 kg	N/A	N/A	N/A	-		0965
1015	13.1 x 6.7 x 3.5 cm	17 x 9.9 x 4.7 cm	1.1 cm	2.4 cm	N/A	0.21 kg	0.54 kg	N/A	IP67		1015
1020	13.5 x 9 x 4.3 cm	17.3 x 12.1 x 5.4 cm	1.8 cm	2.4 cm	0.25 kg	0.25 kg	0.34 kg	-23 / 93° C	IP67		1020
M40	15.2 x 9.7 x 5.3 cm	17.3 x 12.7 x 6.6 cm	2 cm	3.6 cm	N/A	0.3 kg	N/A	-23 / 93° C	IP67		M40
1050	16 x 9.3 x 7 cm	20.3 x 12.9 x 7.9 cm	1.8 cm	4.9 cm	0.38 kg	0.37 kg	0.79 kg	-23 / 93° C	IP67		1050
1030	16.2 x 6.7 x 5.2 cm	19.1 x 9.8 x 6.2 cm	1.8 cm	3.2 cm	0.28 kg	0.27 kg	0.45 kg	-23 / 93° C	IP67		1030
1040	16.5 x 9.8 x 4.4 cm	19.1 x 12.9 x 5.4 cm	1.8 cm	2.4 cm	0.32 kg	0.32 kg	0.57 kg	-23 / 93° C	IP67		1040
R20	18 x 8.6 x 5 cm	22.8 x 12.3 x 7.3 cm	N/A	N/A	N/A	0.6 kg	0.7 kg	-23 / 93° C	IP68		R20
M50	18.5 x 10.9 x 6.1 cm	20.6 x 14 x 7.4 cm	2 cm	4.4 cm	N/A	0.4 kg	N/A	-23 / 93° C	IP67		M50

PROTECTOR CASE™ COLOURS AVAILABLE



* These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

SMALL CASES

CAT. NO.	INTERIOR DIMENSIONS	EXTERIOR DIMENSIONS	LID DEPTH	BOTTOM DEPTH	WEIGHT WITH FOAM	WEIGHT WITHOUT FOAM	BUOYANCY MAXIMUM	TEMPERATURE RANGE (Min/Max)	CERTIFICATES	TREKPAK™	PADDED DIVIDERS	RUBBERISED HANDLES	PANEL FRAMES	PERSONALISED NAMEPLATE	LID ORGANISER	WHEELS	COLOURS	CAT. NO.
1120	18.5 x 12.1 x 8.5 cm	21.4 x 17.2 x 9.8 cm	1.3 cm	6.5 cm	0.65 kg	0.61 kg	2.27 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G				O					1120
R40	19.4 x 11.9 x 4.8 cm	25 x 15.5 x 7.3 cm	N/A	N/A	0.8 kg (with trays)	N/A	1.1 kg	-23/93 °C										R40
1060	21 x 10.8 x 5.7 cm	25.1 x 14.2 x 6.7 cm	1.8 cm	3.7 cm	0.47 kg	0.45 kg	1.1 kg	-23/93 °C										1060
1150	21.1 x 14.7 x 9.5 cm	24 x 19.8 x 10.9 cm	1.9 cm	7.3 cm	0.79 kg	0.73 kg	3.63 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G				O					1150
M60	21.6 x 10.9 x 6.9 cm	23.6 x 15.2 x 8.1 cm	2 cm	5.1 cm	N/A	0.5 kg		-23/93 °C										M60
R60	22.6 x 13.6 x 7.5 cm	28.3 x 17.4 x 9.9 cm	N/A	N/A	1.1 kg (with trays)	N/A	2.2 kg	-40 / 99° C										R60
1300	23.3 x 17.8 x 15.6 cm	27.2 x 24.8 x 17.5 cm	3 cm	12.6 cm	1.6 kg	1.4 kg	5.6 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G				O					1300
1200	23.6 x 18.1 x 10.5 cm	27.1 x 24.8 x 12.3 cm	3 cm	7.4 cm	1.2 kg	1.2 kg	5.45 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G				O					1200
1170	26.8 x 15.3 x 8 cm	29.6 x 21.2 x 9.6 cm	2.7 cm	5.3 cm	0.95 kg	0.89 kg	3.29 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G									1170
1400	30 x 22.5 x 13.2 cm	34 x 29.5 x 15.2 cm	3 cm	10.2 cm	2 kg	1.8 kg	9.1 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G • ATA 300				O	O				1400








PROTECTOR CASE™
COLOURS AVAILABLE



O = Optional accessory

* These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

LAPTOP CASES

CAT. NO.	INTERIOR DIMENSIONS	EXTERIOR DIMENSIONS	LID DEPTH	BOTTOM DEPTH	WEIGHT WITH FOAM	WEIGHT WITHOUT FOAM	BUOYANCY MAXIMUM	TEMPERATURE RANGE (Min/Max)	CERTIFICATES	TREKPAK™	PADDED DIVIDERS	RUBBERISED HANDLES	PANEL FRAMES	PERSONALISED NAMEPLATE	LID ORGANISER	WHEELS	COLOURS	CAT. NO.
1430	34.4 x 14.6 x 29.7 cm	41.7 x 22.1 x 33.4 cm	5.1 cm	24.6 cm	2.95 kg	2.54 kg	26.8 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		O	S	O	O	O			1430
1470	39.9 x 27.2 x 9.8 cm	42.9 x 33.6 x 11.4 cm	3.7 cm	6.1 cm	2.5 kg	1.94 kg	11.3 kg	-40 / 99° C	MIL-STD-810G			S	O	O				1470
1440	43.4 x 19.1 x 40.6 cm	50 x 30.5 x 45.7 cm	5.1 cm	35.6 cm	7.48 kg	6.58 kg	43.2 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		O	S		O	O	S		1440
1490	45.1 x 28.9 x 10.5 cm	50.5 x 35.4 x 11.9 cm	3.8 cm	6.7 cm	2.95 kg	2.48 kg	18.6 kg	-40 / 99° C	DEF STAN 81-42 • MIL-STD-810G			S	O	O	O			1490
1490CC1	45.1 x 28.9 x 10.5 cm	50.5 x 35.4 x 11.9 cm	3.8 cm	6.7 cm	2.9 kg	2.5 kg	18.6 kg	-40 / 99° C	DEF STAN 81-42 • MIL-STD-810G			S	O	O	S			1490CC1
1495	47.9 x 33.3 x 9.7 cm	54.9 x 43.8 x 12.4 cm	2.8 cm	6.8 cm	3.8 kg	3.28 kg	20.5 kg	-40 / 99° C	IP67 • DEF STAN 81-41/STANAG 4280			S		O	O			1495
1495CC1	47.9 x 33.3 x 9.7 cm	54.9 x 43.8 x 12.4 cm	2.8 cm	6.8 cm	3.8 kg	3.3 kg	20.5 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G			S		O	S			1495CC1




















PROTECTOR CASE™
COLOURS AVAILABLE



S = Standard feature | O = Optional accessory

* These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.

MEDIUM CASES

CAT. NO.	INTERIOR DIMENSIONS	EXTERIOR DIMENSIONS	LID DEPTH	BOTTOM DEPTH	WEIGHT WITH FOAM	WEIGHT WITHOUT FOAM	BUOYANCY MAXIMUM	TEMPERATURE RANGE (Min/Max)	CERTIFICATES	TREKPAK™	PADDED DIVIDERS	RUBBERISED HANDLES	PANEL FRAMES	PERSONALISED NAMEPLATE	LID ORGANISER	WHEELS	COLOURS	CAT. NO.
1450	37.2 x 26 x 15.5 cm	41.8 x 33 x 17.3 cm	4.4 cm	11.1 cm	2.9 kg	2.5 kg	13.61 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G • MIL C-4150J	O	O	S	O	O				1450
1500	42.5 x 28.4 x 15.5 cm	47 x 35.7 x 17.6 cm	4.6 cm	10.9 cm	3.6 kg	3.2 kg	22.68 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G • ATA 300 • MIL C-4150J	O	O	S	O	O	O			1500
0340	45.7 x 45.7 x 45.7 cm	52.1 x 52.1 x 48.9 cm	11.4 cm	34.3 cm	13.5 kg	10.89 kg	100 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		O			O	O			0340
1520	45.9 x 32.7 x 17.1 cm	50.2 x 40.1 x 18.8 cm	4.5 cm	12.5 cm	4.24 kg	3.76 kg	28.6 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G • MIL C-4150J		O	S	O	O				1520
1460	47.1 x 25.2 x 27.7 cm	53 x 32.3 x 32.4 cm	12.5 cm	15.3 cm	5.66 kg	3.97 kg	37.19 kg	-40 / 99° C	IP67 • MIL-STD-810G			S						1460
1460TOOL	47.1 x 25.2 x 27.7 cm	53 x 32.3 x 32.4 cm	12.5 cm	15.3 cm	5.9 kg (with trays)	N/A	37.2 kg	-40 / 99° C	IP66 • MIL-STD-810G									1460TOOL
1460EMS	47.1 x 25.2 x 27.7 cm	53 x 32.3 x 32.4 cm	12.5 cm	15.3 cm	8.26 kg (with trays)	N/A		-40 / 99° C	IP66 • MIL-STD-810G									1460EMS
1550	47.3 x 36 x 19.6 cm	52.5 x 43.7 x 21.3 cm	4.4 cm	14.9 cm	5.4 kg	4.8 kg	31.7 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G • MIL-STD.810F • MIL C-4150J • ATA 300 • MIL C-4150J	O	O	S	O	O				1550
1510	50.2 x 27.9 x 19.3 cm	55.9 x 35.1 x 22.9 cm	4.5 cm	14.7 cm	6.2 kg	5.4 kg	29.1 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G	O	O	S		O	O	S		1510
1510M	50.2 x 27.9 x 19.3 cm	59.8 x 36.5 x 27 cm	4.5 cm	14.7 cm	8.1 kg	7.4 kg	N/A	-40 / 99° C	IP57 • MIL-STD-810G	O	O	S		O	O	S		1510M
1510SC	50.2 x 27.9 x 19.3 cm	55.9 x 35.1 x 22.9 cm	4.5 cm	14.7 cm	6.2 kg	5.4 kg	29.1 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		S	S			S	S		1510SC
1510LOC	50.2 x 27.9 x 19.3 cm	55.9 x 35.1 x 22.9 cm	4.5 cm	14.7 cm	6.2 kg	5.4 kg	29.1 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G			S			S	S		1510LOC
1510LFC	50.2 x 27.9 x 19.3 cm	55.9 x 35.1 x 22.9 cm	4.5 cm	14.7 cm	6.2 kg	5.4 kg	29.1 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G			S			S	S		1510LFC
1560	50.6 x 38 x 22.9 cm	56.1 x 45.5 x 26.5 cm	5.1 cm	17.8 cm	9.1 kg	7.7 kg	52.16 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G	O	O	S		O	O	S		1560
1560M	50.6 x 38 x 22.9 cm	60.4 x 46.6 x 30.7 cm	5.1 cm	17.8 cm	11 kg	9.7 kg	N/A	-40 / 99° C	IP57 • MIL-STD-810G	O	O	S		O	O	S		1560M
1560SC	50.6 x 38 x 22.9 cm	56.1 x 45.5 x 26.5 cm	5.1 cm	17.8 cm	8.2 kg	7.7 kg	52.2 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G			S			S	S		1560SC
1560LOC	50.6 x 38 x 22.9 cm	56.1 x 45.5 x 26.5 cm	5.1 cm	17.8 cm	8.2 kg	7.7 kg	52.2 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G			S			S	S		1560LOC
1560LFC	50.6 x 38 x 22.9 cm	56.1 x 45.5 x 26.5 cm	5.1 cm	17.8 cm	8.2 kg	7.7 kg	52.2 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G			S			S	S		1560LFC
0350	50.8 x 50.8 x 50.8 cm	57.2 x 57 x 54 cm	12.7 cm	38.1 cm	14.52 kg	11.79 kg	122 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		O			O	O			0350





































PROTECTOR CASE™
COLOURS AVAILABLE



S = Standard feature | O = Optional accessory

* These colours are available upon minimum quantities, as well as other configurations.
Check with your Customer Service representative for further details.

LARGE CASES

CAT. NO.	INTERIOR DIMENSIONS	EXTERIOR DIMENSIONS	LID DEPTH	BOTTOM DEPTH	WEIGHT WITH FOAM	WEIGHT WITHOUT FOAM	BUOYANCY MAXIMUM	TEMPERATURE RANGE (Min/Max)	CERTIFICATES	TREKPAK™	PADDED DIVIDERS	RUBBERISED HANDLES	PANEL FRAMES	PERSONALISED NAMEPLATE	LID ORGANISER	WHEELS	COLOURS	CAT. NO.
0450	Varies by drawer configuration	60.8 x 37.5 x 45.6 cm	N/A	N/A	21.95 kg	N/A	N/A	-40 / 99° C	-							S		0450
1620	54.3 x 41.4 x 31.9 cm	66.5 x 49.2 x 35.2 cm	5.2 cm	26.7 cm	11.8 kg	11.1 kg	68 kg	-40 / 99° C	IP67 • MIL STD 810G • MIL C-4150J		O	S		O		S	    *	1620
1620M	54.6 x 41.7 x 31.9 cm	66.5 x 58.4 x 39.6 cm	5.1 cm	26.7 cm	14.3 kg	12.7 kg	N/A	-40 / 99° C	IP57 • MIL STD 810G		O	S		O		S		1620M
1600	54.6 x 42 x 20.2 cm	61.8 x 49.4 x 22.2 cm	4.4 cm	15.5 cm	6.4 kg	5.9 kg	53.07 kg	-40 / 99° C	IP67 • MIL-STD-810G • ATA 300 • MIL C-4150J	O	O	S		O	O		   	1600
1610	55.1 x 42.2 x 26.8 cm	62.8 x 49.7 x 30.3 cm	5.2 cm	21.6 cm	10.2 kg	9.1 kg	54.4 kg	-40 / 99° C	IP67 • MIL STD 810F • MIL STD 810G	O	O	S		O		S	    *	1610
1610M	55.3 x 42.4 x 27 cm	66.5 x 58.4 x 34.7 cm	5.2 cm	21.8 cm	13.2 kg	11.9 kg	N/A	-40 / 99° C	IP57 • MIL STD 810G	O	O	S		O		S		1610M
1640	60.2 x 61 x 35.3 cm	69.1 x 69.9 x 41.4 cm	5.1 cm	30.2 cm	17.24 kg	15.42 kg	166 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		O			O		S		1640
0370	61 x 61 x 61 cm	67.3 x 67.3 x 64.1 cm	12.7 cm	48.3 cm	18.6 kg	14.5 kg	211 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		O			O	O	O	  *	0370
1630	70.4 x 53.3 x 39.4 cm	79.5 x 61.5 x 44.4 cm	8.3 cm	30.8 cm	16.33 kg	14.06 kg	159 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD.810G • ATA 300 • MIL C-4150J		O			O	O	S	   *	1630
1670	71.4 x 41.9 x 23.3 cm	78.8 x 49.3 x 28.4 cm	4.6 cm	18.8 cm	11.8 kg	10.4 kg	82.6 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G • MIL C-4150J							S		1670
1660	71.6 x 50.2 x 44.8 cm	80 x 58.1 x 48.3 cm	8.9 cm	35.9 cm	19.1 kg	15.5 kg	159 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		O			O	O	S	    *	1660
1650	72.2 x 44.2 x 27 cm	80.1 x 52.1 x 31.7 cm	4.6 cm	22.5 cm	12.73 kg	10.9 kg	82.1 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G	O	O	S		O	O	S	   *	1650
1690	76.5 x 63.8 x 39 cm	84.9 x 72.1 x 44.8 cm	7.3 cm	30.8 cm	19.5 kg	15.42 kg	186 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G		O			O	O	S	   *	1690
1730	86.4 x 61 x 31.8 cm	95.3 x 68.9 x 36.5 cm	6.4 cm	25.4 cm	17.24 kg	13.61 kg	189 kg	-40 / 99° C	IP67 • MIL-STD-810G					O		S	   *	1730
0500	88.8 x 46.9 x 64.1 cm	101.5 x 59.6 x 72.8 cm	5.7 cm	58.4 cm	26.58 kg	22.68 kg	354 kg	-40 / 99° C	-					O	O			0500








PROTECTOR CASE™
COLOURS AVAILABLE



S = Standard feature | O = Optional accessory

* These colours are available upon minimum quantities, as well as other configurations.
Check with your Customer Service representative for further details.

LONG CASES

CAT. NO.	INTERIOR DIMENSIONS	EXTERIOR DIMENSIONS	LID DEPTH	BOTTOM DEPTH	WEIGHT WITH FOAM	WEIGHT WITHOUT FOAM	BUOYANCY MAXIMUM	TEMPERATURE RANGE (Min/Max)	CERTIFICATES	TREKPAK™	PADDED DIVIDERS	RUBBERISED HANDLES	PANEL FRAMES	PERSONALISED NAMEPLATE	LID ORGANISER	WHEELS	COLOURS	CAT. NO.
1700	90.8 x 34.3 x 13.3 cm	96.8 x 40.6 x 15.5 cm	4.4 cm	8.9 cm	7.7 kg	7.3 kg	62.1 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G • MIL C-4150J							S		1700
1740	104.1 x 32.8 x 30.8 cm	112.2 x 40.9 x 35.6 cm	6.5 cm	24.3 cm	12.25 kg	9.98 kg	121.11 kg	-40 / 99° C	MIL-STD-810G					O		S		1740
1780	104.4 x 54.7 x 37.8 cm	114 x 64.3 x 41.9 cm	19.3 cm	18.5 cm	22.20 kg	17.4 kg	226.8 kg	-40 / 99° C	DEF STAN 81-42 • MIL-STD-810G					O		S		1780
1720	106.2 x 34.5 x 13.5 cm	113 x 40.8 x 15.9 cm	4.4 cm	8.9 cm	10.5 kg	8.3 kg	73 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G					O		S		1720
0550	120.8 x 61.1 x 44.9 cm	129.7 x 70 x 57.9 cm	8.1 cm	36.8 cm	43.09 kg	35.92 kg	371.95 kg	-40 / 99° C	IP55 • MIL-STD-810G					O		O		0550
1750	128.3 x 34.3 x 13.3 cm	134.6 x 40.6 x 15.5 cm	4.4 cm	8.9 cm	11.6 kg	10.7 kg	85 kg	-40 / 99° C	IP67 • DEF STAN 81-42 • MIL-STD-810G					O		S		1750
1770	138.6 x 39.6 x 21.9 cm	145.8 x 46.9 x 28.5 cm	4.8 cm	17.1 cm	18.8 kg	16.3 kg	127.01 kg	-40 / 99° C	MIL-STD-810G							S		1770

PROTECTOR CASE™
COLOURS AVAILABLE



S = Standard feature | O = Optional accessory

* These colours are available upon minimum quantities, as well as other configurations. Check with your Customer Service representative for further details.



BASE PROTECTION

ACCESSORIES

Photo by Gauthier Courquin & Yannick Rousseau



PICK N PLUCK™ FOAM

An easy, do-it-yourself system for the interior of the case. Layers of foam are pre-scored in 1,27 cm or 2,54 cm cubes. Simply lay your equipment on the foam, tape or chalk to mark the foam, and pluck away. Always allow at least 2,5 cm of foam between your equipment and the case wall.

The following cases ship with solid foam instead of Pick N Pluck™ Foam: 1700, 1720, 1750.



PADDED DIVIDERS

An alternative to Pelican™ foam is our optional Padded Divider Sets. The compartments are connected with Velcro® so you can easily change the configuration according to your needs.

CASE	LAYERS	CASE WITH DIVIDERS (CAT. NO.)	DIVIDER SET ONLY (CAT. NO.)
1450	1	1454	1455
1500	1	1504*	1505*
1510	1	1514*	1515*
1520	1	1524	1525
1550	1	1554*	1555*
1560	1	1564*	1565*
1600	1	1604	1605
1610	1	1614	1615
1620	2	1624	1625
1630	2	1634	1635
1640	2	1644	1645
1650	1	1654*	1655*
1660	2	1664	1665
1690	2	1694	1695
0340	2	0344	0345
0350	2	0354	0355
0370	2	0374	0375




* These cases/sets come with new high-visibility yellow dividers. All others with standard black dividers.



TREKPAK™ DIVIDERS*

The TrekPak™ system uses pre-installed wall sections, divider panels, locking pins and an infallible cutting tool. Just lay your gear in the case, measure and cut the divider sections and lock them in place with the steel U-pins.

Trekpak™ is available for select models.



LID PROTECTION



ACCESSORIES

Photo by Eduardo Vinas



LID ORGANISERS

Made of simulated leather or ballistic nylon with nylon zippers. A wide variety of pocket sizes protect and keep your gear organised. They install easily with Velcro® strips (included).

	MESH	COMPUTER	PHOTO	EMS
CASE				
1430			1439 Photo ^A	
1440	1449 Mesh ^A			
1490		1498 Computer ^B		
1495		1495 Computer ^B		
1500	1509 Mesh		1508 Photo ^B	1505 EMS ^B
1510	1519 Mesh ^A			
1520	1509 Mesh		1508 Photo ^B	
1550				1555 EMS ^B
1560	1569 Mesh			
1600	1609 Mesh ^B			1605 EMS ^A
1610	1609 Mesh ^B			
1620	1609 Mesh ^B			
1630	1639 Mesh ^A			
1640	0379 Mesh ^A			
1650	1659 Mesh ^A			
1660	1669 Mesh ^A			
1690	1699 Mesh ^A			
0340	0349 Mesh ^A			
0350	0359 Mesh ^A			
0370	0379 Mesh ^A			

A= With mounting screws B= With mounting Velcro®



EZ-CLICK™ MOLLE PANEL

The first lid organiser of its kind that can quickly be released and swapped out without tools. Engineered to fit in the 1510, 1560 and 1535 Peli cases, the panel is compatible with user-supplied MOLLE pouches and Velcro™ brand straps.



TSA LOCK



NAMEPLATES



LID STAYS



**PELI DESICCANT
(SILICA GEL)**



CASTER WHEEL KIT



CARD HOLDER



PALLET RISER

OTHER

ACCESSORIES



SPECIAL APPLICATIONS



CUSTOM FOAM SOLUTIONS


Custom foam and extreme solutions such as deck mount suspension systems will keep your delicate items protected on the inside.



PANEL FRAMES

Many Peli cases can be adapted for use with electronic interface panels by using a Panel Frame. Pre-drilled holes and stainless steel screws make fabricating a custom case a fast and accurate proposition.

A polymer o-ring seals the panel so the base of the case remains watertight, even with the lid open.

The following cases are adaptable for use with panel frames: 1120, 1150, 1200, 1300, 1400, 1430, 1450, 1470, 1490, 1500, 1520, 1550 (search for the icon )



- O-ring
- Panel Frame
- Attachment Hardware

See how to mount a panel frame here:



ELECTRONIC INSTALLATIONS

Peli Case allows customisation for electronics. The copolymer material can be machined, drilled and sanded smooth. This makes the Peli Case suitable for use with bulkhead connectors.



WE CUSTOMISE YOUR LOGO

Personalise your case with your company logo or have your name engraved on the nameplate. Logos can be applied in multiple colours as a Mylar® decal or as a vibrant fade-resistant, scratch-resistant hot-stamped ink.

374
14.72



**EMEI HEADQUARTERS
PELI PRODUCTS, S.L.U.**
C/ Provença, 388 Planta 7
08025 Barcelona • Spain
Tel +34 934 674 999

**PELI PRODUCTS
FRANCE S.A.S.**
20/22 Rue des Petits Hôtels
75010 Paris • France
Tel +33 (0)1 44 83 95 63

**PELI PRODUCTS
GERMANY GmbH**
Neudorfer Strasse 285 C
09474 Crottendorf • Germany
Tel +49 (0)37344 313999

381.5